



Self-adhered Membrane

Rollon delivers an easy-to-install, breathable building wrap solution.

Rollon preserves your building. It doesn't allow moisture in, while the water vapor can escape the wall through its pores. Your structure stays dry and stable.

Available in both mechanically attached and self-adhered forms, **rollon** is the perfect solution for exterior walls of residential and commercial construction.

Key features & Benefits:

- self-adhered for fast and easy installation
- roll on! No primer is needed
- compatible with most wall substrates and fenestration materials: wood, DensGlass, concrete, brick, steel, aluminum, and vinyl
- manufactured using high-end technology with 99% precision on membrane thickness and pore dimensions

Physical Properties

Property	Value
Color	Red
Roll Dimensions	59" x 164' (1.5m x 50m)
Roll coverage	807 ft ² (75 m ²)
Weight	0.91 oz/ft ² (278 g/m ²)
Primer	No primer is required
UV Exposure	90 days
Service temperature	- 40°F to 176°F (-40°C to 80°C)
VOC	None

	Property	Value	Test method
Water	Water resistance	No leakage	AATCC 127
Air	Air barrier qualification test	0.004 L/s-m ² @ 75 Pa	ASTM E2178
Fire	Fire test	Class A	ASTM E84
	Flame spread index	15	
	Smoke developed index	50	
Strength	Tensile properties		ASTM D828
	MD	37 lb/in	
	XMD	25 lb/in	